<b>MAC:CFX</b> <sup>®</sup>	Material Safety Data Sheet	Page : 1 Revision nr. : 1 Date: 14/2/2011
MAGICFX Flame Fluid		Supersedes : 2/5/2009 Code : 337001

Yellow, Red, Green, Blue



Xn Harrmful ( only by Blue ) ( F+) Highly flammable

### **1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY**

**Responsible for distribution:** In case of emergency: MAGIC FX BV Industrieweg 16 NL-5281 RW Boxtel THE NETHERLANDS The Netherlands: TEL: +31(0)411-635013 TEL: 030 / 274 88 88 FAX: +31(0)411-635012 National Poisoning Information Center - Bilthoven Identification of the product \* - Type of product : Complex substance . - Use of product : Several industrial applications ( Solvent , ...). Company identification : See heading of Material Safety Data Sheet. Emergency phone number : See heading of Material Safety Data Sheet.

#### 2. HAZARD IDENTIFICATION

Highly Flammable

: R11 – Highly flammable.

### 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Name component(s)	Weight %	CAS nr / EC nr / EC annex nr	Syı	mbol(s)	R-Phrase(s)
Ethanol : Limit value (Belgium) Limit value (TWA 8 h) (The Netherla Limit value (TWA 15 min) (The Neth	ands) : 200	64-17-5 / 200-578-6 / 603-002-00-5 00 ppm (1907 mg/m <sup>3</sup> ) (2007) 0 ppm ( 260 mg/m <sup>3</sup> ) (2008) (H) 00 ppm (1900 mg/m <sup>3</sup> ) (2008) (H)	/	F	11
Methanol :	< 3 %	67-56-1 / 200-659-6 / 603-001-00-X	/	F,T	11-23/24/25-39/ 23/24/25
Limit value (Belgium)	: 200	) ppm (266 mg/m³) (2007) (D)			
Short time value (Belgium)	: 250	) ppm (333 mg/m <sup>3</sup> ) (2007) (D)			
Limit value (TWA 8 h) (The Netherla	ands) : 200	) ppm (260 mg/m³) (2007) (H)			
Limit value (TWA 15 min) (The Neth	nerlands) : 400	) ppm (520 mg/m³) (2007) (H)			
Chloride	< 0,3 %	10125-13-0 / 231-210-2		Xn	20-22 / 36-38

The full text of the R-phrases is in chapter 16.

(D) The mention "D" means that the absorption of the agent by skin, mucous membranes or eyes constitues an important part of the total exposition. This aborsption can be the consequence of direct contact as well as his presence in the air.

(H) The addition of an "H" indicates that the substance is relative easily absorped by the skin.

#### 4. FIRST AID MEASURES

General	: In case of doubt or persistent symptoms, call a physician.
	Never give anything by mouth to an unconscious person.
First Aid Measures	
- Inhalation	: Remove victim into fresh air.
	Allow the affected person to rest.
	If not breathing, give artificial respiration.
	Consult a doctor.
- Skin Contact	: Remove contaminated clothing.
	Rinse skin immediately with plenty of water. (shower if necessary).
	Consult doctor if irritation develops.
- Eye Contact	: Rinse immediately thoroughly and long (at least 15 min.) with plenty of water.
	Remove contact lenses.
	Consult eye doctor.
	Do not use a neutralisation agent.
- Ingestion	: DO NOT INDUCE VOMITING. Rinse mouth with water.
	Seek medical advice.
*	

**MAGIC FX** 



Material Safety Data Sheet

Page : 2 Revision nr. : 1 Date: 14/2/2011

**MAGICFX Flame Fluid** 

Yellow, Red, Green, Blue

5. FIRE-FIGHTING MEASURES

Extinguishing Media - Suitable	: Alcohol resistant foam , Powder , Carbon dioxide , Water spray .	
Special Procedures	: Apply water spray or fog to cool nearby equipment. Avoid fire-fighting water to enter environment.	
Special Exposure Hazards	: Fire may liberate carbon oxides (CO) and smoke.	
Special Protective Equipment for Firefighters	: Use self-contained breathing apparatus when in close proximity to fire.	
6. ACCIDENTAL RELEASE MEAS	SURES	
Personal Precautions	: Eliminate every possible source of ignition (open fire, sparks, smoking,). Evacuate all personnel immediately and ventilate area. Avoid breathing vapour and contact with skin, eyes and clothing. Wear recommended personal protective equipment. (See chapter 8).	
Environmental Precautions	: Shut off leaks if without risks. Dike in the spilled product as much as possible with inert material. Prevent entry of product in public water, sewers or soil. Notify authorities if product enters sewers or public waters.	
* Methods for Cleaning Up	: Collect the spillage in closable, suitable disposal containers. Clean up any spills as soon as possible, using an inert absorbent material. For the removal of the waste product, see chapter 13. Residue is to be washed down with plenty of water. Drain off rinsing water into sewers.	
7. HANDLING AND STORAGE		
Handling	: Avoid breathing vapour and contact with skin, eyes and clothing. Wear recommended personal protective equipment. (See chapter 8).	
Protection against Fire and Explosion	<ul> <li>Eliminate every possible source of ignition (open fire, sparks, smoking,).</li> <li>With a temperature equal to or higher than the flash point, the mixture steam-air may create a highly flammable and explosive mixture.</li> <li>Do not use compressed air to either agitate or transfer contents of storage containers (tanks) / shipping drums containing this material.</li> <li>Always use explosionproof electrical equipment.</li> <li>Use spark-arm implement.</li> </ul>	
Storage	: Keep only in the original, safely locked container in a cool, well ventilated and fireproof place. Store away from all heat sources, including direct sunlight. Keep away from : Oxidizing agents	
8. MEASURES EXPOSURE CON	TROL / PERSONAL PROTECTION	
Engineering Measures	: Ventilate area.	
Industrial Hygiene	: When using, do not eat, drink or smoke. Emergency eye wash fountains and showers should be available in the immediate	
Occupational Exposure Limits	vicinity of any potential exposure. : For components: see chapter 3.	
Personal Protection Equipment - Respiratory Protection	: Ventilation , Local exhaust . CE-Approved organic vapour and solvent respirator (Type A, brown).	
- Hand Protection	: Gloves ( Butyl rubber , Neoprene ,)	
- Eye Protection	: Closed safety glasses or face shield.	
- Skin and Body Protection	: Suitable protective clothing.	



Page : 3 Revision nr. : 1 Date: 14/2/2011

MAGICFX FLame Fluid

Yellow, Red, Green, Blue

Supersedes : 2/5/2009 Code : 337001

9. PHYSICAL AND CHEMICAL PROPERTIES

9. PHYSICAL AND CHEMICAL P	ROPERTIES
Physical State (20°C) Form/Colour Odour	: Liquid . : Colourless . : Characteristic odour .
pH value Boiling Point/Range (1013 hPa) Congealing/Melting point	: Not applicable. : 65 - 78 °C : -117 °C
Flash point Fire hazard Auto-ignition temperature	: 12 °C : P1 : > 350 °C
Explosion limits in air Vapour pressure (20°C) Relative vapour density (air=1)	: 3,4 - 19 vol.% : 58,5 mbar : 1,6
Solubility in water Soluble in Log P Octanol/Water (20°C)	: Complete solubility. : Solvents . : -0,3 to 0,7
Relative density (water=1) Viscosity	: app. 0,8 : 0,0012 Pa.s
Evaporation rate % Volatiles (by weight)	: > 8 ( Ether = 1) : > 99
10. STABILITY AND REACTIVITY	1
Stability Conditions to avoid	: Stable at normal circumstances. : High temperatures .
Materials to avoid Hazardous Decomposition Products	: Oxidizing agents . : Fire may liberate carbon oxides (CO) and smoke.
11. TOXICOLOGICAL INFORMA	ΓΙΟΝ
Acute toxicity - Inhalation	<ul> <li>May cause irritation of respiratory tract.</li> <li>Exposure to high concentrations may cause lowering of consciousness.</li> <li>Symptoms include: Cough, Headache, Drowsiness, Dizziness.</li> <li>For components:</li> <li>• Ethanol : LC50 (Rat, inhalation, 4 h) : &gt; 8000 mg/l</li> <li>• Methanol : LC50 (Rat, inhalation, 4 h) : 80 - 130 mg/l</li> </ul>
- Skin contact	: May be irritating for the skin. Symptoms include: Redness . : For components: : • Ethanol : LD50 (Rabbit, dermal) : > 2000 mg/kg • Methanol : LD50 (Rabbit, dermal) : 20000 mg/kg
- Eye contact	: May be irritating to eyes. Symptoms include: Redness , Pain .
- Ingestion	<ul> <li>After swallowing, some drops of liquid can enter the longs (aspiration), which may cause pneumonia.</li> <li>Symptoms include: Headache, Dizziness, Drowsiness.</li> <li>For components:</li> <li>• Ethanol : LD50 (Rat, oral) : &gt; 2000 mg/kg</li> <li>• Methanol : LD50 (Rat, oral) : &gt; 5000 mg/kg</li> </ul>
Other toxicological information	: May cause damage to liver after ingestion. : For components: : Information on the webaddress http://ecb.jrc.it/ESIS (see IUCLID Data Sheets).
Sensibilization Carcinogenicity Mutagenicity Teratogenicity Specific effects on human health	<ul> <li>No sensibilsation .</li> <li>Not carcinogenic .</li> <li>Not mutagenic .</li> <li>Not teratogenic .</li> <li>Not teratogenic .</li> <li>The Netherlands : Ethanol is included in the SZW list:</li> <li>Non-limitative list of reproduction toxic substances to which the additional registration obligation applies as referred to in Article 4.2a, second paragraph of the Working conditions decree; Category 1 "fertility", Category 1 "development", Breast feeding.</li> </ul>



Page : 4 Revision nr. : 1

Supersedes : 2/5/2009

Code : 337001

Date: 14/2/2011

# MAGICFX Flame Fluid

### Yellow, Red, Green, Blue

#### 12. ECOLOGICAL INFORMATION

This product is classified as a Volatile Organic Mobility Persistence and degradability	c Component according to Directive 1999/13/EC. : Product completely soluble in water. : Ethanol : Easily biologically degradable. ( BOD = 5, COD > 0,5)
Bioaccumulation Ecotoxicity	: Bioaccumulation not expected . : For components: : • Ethanol : LC50 (Fish, 48 h) : > 100 mg/l (Leuciscus idus) • Ethanol : EC50 (Daphnia magna, 24 h) : > 100 mg/l • Methanol : LC50 (Fish, 96 h) : > 10000 mg/l (Pimephales promelas) • Methanol : EC50 (Daphnia magna, 24 h) : > 10000 mg/l
Other ecological information	: For components: : Information on the webaddress http://ecb.jrc.it/ESIS (see IUCLID Data Sheets).
WGK class (Germany)	: 1 ( Weak water pollutant ).
Water damaging (The Netherlands) Decontamination exertion ( The Netherlands )	: 11 : B
<b>13. DISPOSAL CONSIDERATIONS</b>	
Waste from residues/Unused products	: The product has to be destroyed according to national or local legislation, by a company specialised in handling hazardous waste products.
Removal contaminated packaging	: Packing is to be used exclusively for the packing of this product. After use, empty and close the packing very carefully. In case of returned packing, the empty packing can be offered back to the supplier.
European list of waste products	: 070104 - Other organic solvents, washing liquids and mother liquors. European waste product code: 'XX XX XX '. This code is assigned on the basis of the most current applications and can not be representative for pollutions which are arisen at the effective use of the product. The producer of the waste has to

	directive 2001/118/EC.
14. TRANSPORT INFORMATION	
Land (Road/Railroad, ADR/RID) - ADR Name - ADR Division - Hazard Label(s) - Danger number - Substance Ident. Number (UN-n°)	: UN 1170 Ethanol solution (Ethyl alcohol solution), 3, II, SP144 : 3 , II : 3 : 33 : 1170
Sea Transport (IMDG) - Product Name - Class - Hazard Label(s) - UN Number - Packaging Group - EmS-N° - Marine pollutant	: UN 1170 Ethanol solution (Ethyl alcohol solution) , 3, II, (12°C) : 3 : 3 : 1170 : II : F-E, S-D : NO

evaluate its process himself and has to grant the appropriate waste coding. See

\*



Page: 5 Revision nr. Date: 14/2/2011

Supersedes : 2/5/2009

Code : 337001

## **MAGICFX Flame Fluid**

Yellow, Red, Green, Blue

# **15. REGULATORY INFORMATION** Name dangerous component(s) : Ethanol Symbol(s) Highly flammable Harmful (only by Blue) : R11 - Highly flammable. **R-Phrases** S-Phrases : S07 - Keep container tightly closed. S16 - Keep away from sources of ignition - No smoking.

: X01 - Reserved for industrial and professional use.

X-Phrases (The Netherlands)

#### **16. OTHER INFORMATION**

This safety data sheet has been drawn up in accordance with the EC Regulation n° 1907/2006. This safety data sheet is exclusively made for industrial/professional use. Classification and labelling in accordance with the Directive 1999/45/EC.

\* Has changed compared to previous revision.

Sources of used key data	: The information contained herein is based on the present state of our knowledge ( ${\sf Producer}(s)$ , Chemical cards ,).
* Changes R-phrases	<ul> <li>: Change of product name .</li> <li>: R11 - Highly flammable.</li> <li>R23/24/25 - Toxic by inhalation, in contact with skin and if swallowed.</li> <li>R36 - Irritating to eyes.</li> <li>R39/23/24/25 - Toxic : danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.</li> <li>R66 - Repeated exposure may cause skin dryness or cracking.</li> <li>R67 - Vapours may cause drowsiness and dizziness.</li> </ul>

This information is to our knowledge correct and complete on the date of issue of this safety data sheet. The information only concerns the product and does not give any guarantee for the quality and the completeness of the properties of the product, or in case of mixing or using in any other process. It remains the responsibility of the user to assure himself that the information is suitable and complete concerning the special use he makes of the product. MAGIC FX denies all responsibility for loss or damage resulting from the use of these data.

End of document